

FEATURES:

- Ideal choices for community, and commercial AC EV charger
- Input: 380Vac
- Stylish, ergonomic and customizable design
- Ip65 rated for indoor/outdoor applications
- Wireless connection for back office management
- Optional wired connection for back office management
- Charging interface: IEC62176-TYPE 2- PLUG FEMALE

ELECTRIC SPECIFICATION:

Model Name	SQX20707A
Input / Output Phase Voltage	Three phase : 3P + N + PE ; 380 VAC ± 10%
Output AC Current	Three phase 63A (1 set)
Frequency	50Hz / 60Hz
Ground Fault Protection	Lost input ground connection
OCP (Over Current Protection)	< 69.3A
OVP (Over voltage Protection)	Phase voltage > 265V
UVP (Under voltage Protection)	Phase voltage < 190V
Residual Current Device	Type AC : IΔn 30 mA Manual recovery after protection triggers
Regulation	IEC 61851-1:2017, IEC 61851-21-2
Charging Plug / Socket (Socket Protection Lock System)	IEC 62196-2:2016 Type 2 Plug Female
Thermal Protection	YES
IP Degrees	Ip55
Storage Temperature	-40°C ~ +70°C
Operating Temperature	-20°C ~ +50°C
Humidity at Operating Condition	95%RH max.
Humidity at Storage Condition	95%RH max.



All specifications are subject to change without notice.

Protections

- OVP/ UVP
- OCP
- OTP

HEADQUARTERS

Monseñor P. Cabrera 5020 - Córdoba, X5008HJP Argentina
Tel.: (54) 351 4770044 / Fax (54) 351 4764576
sales@dta-sa.com

For more information visit:
<http://www.dta-sa.com/>

