


Solid State Power Amplifier (SSPA)



M O D E L
H P A 2 0 0 - D T A

DESCRIPTION

DTA offers the model of Solid State Power Amplifier HPA200-DTA, designed to provide the highest performance for satellite uplink applications. Its great linearity, protections and control options gives to this equipment the desired flexibility on the SATCOM ground stations

FEATURES

- 200 W Linear Power
- Wide Bandwidth
- 85 dB Gain typical
- Broad gain adjustment, 65 dB to 85 dB in 0.25 dB steps
- Input Overload Protection
- Over-temperature, over-current and high output VSWR safety protection
- Output Power Metter
- Forward and reflected power internal monitor
- Five Rack Units Height for 19" Rack Mounting
- Switch Mode Power Supply
- Ethernet Interface
- Remote control via Web Browser
- Local control via front panel keyboard
- Local control by PC via the RS-232 connection
- Microprocessor-based monitor and control system
- Can operate in a redundant configuration

All specifications are subject to change without notice.

ELECTRICAL SPECIFICATIONS

Frequency range :	2000 a 2120 Mhz
Output power (at 1dB compression) :	200 watts CW
Gain :	>85 dB
Gain Adjust Range :	20 dB
Gain Step :	0.25 dB
Output Impedance :	50 ohms
Input VSWR :	< 1.75:1
Admisible output VSWR :	< 2:1
nominal Input Power :	- 33 dBm
Maximun Input Power (no damage) :	0 dBm
Noise Figure :	< 15 dB

GENERAL SPECIFICATIONS:

RF Input Connector :	N female
Input Impedance :	50 ohms
RF output Connector :	N female
Primary power :	220 Vac +/- 10% 50 Hz
Cooling :	forced

PHYSICAL:


Chasis :	8.75" x 19" x 29" Rack Mounting
Weight :	33 kg

ENVIROMENTAL:

Ambient operating temperature :	0 °C to 40 °C
---------------------------------	---------------

All specifications are subject to change without notice.

BLOCK DIAGRAM



HEADQUARTERS

Monseñor P. Cabrera 5020 - Córdoba, X5008HJP Argentina
Tel.: (54) 351 4770044 / Fax (54) 351 4764576
sales@dta-sa.com

USA Office

GM Systems LLC
27 Kim Place, Kings Park, N.Y. 11754-5025
Tel.: 631-269-3820
terlizzi@gmsystems.com

ISRAEL Office

Ultram Technologies Ltd.
58 Hameyasdim Street, Moshav Mazor, 73160
Tel.: (972) 03 9331696
sales@ultramtech.co.il

for more information visit:
<http://www.dta-sa.com/>

